

## Professional Gravel Path Renovators - WE series

**WE 110 M-DP** - Gravel Path Renovator 110cm working width

**WE 150 M-DP** - Gravel Path Renovator 150cm working width

For Tractors 20 - 50HP



- This is our range of heavy duty, professional gravel path renovators with mechanical drive for renovating water bound surfaces.
- The specially designed knives are designed to de-compact the gravel and lift weeds to the surface in one operation.
- An adjustable roller follows behind to level the surface once the knives have been through it, giving an even finish.
- The machine can be used with different tools depending on the type of surface and the material in the layer below. These accessories are detailed in the following pages.
- The depth and angle of the knives is finely adjusted by either the castor wheels or roller adjuster to position the knives for precise renovation.
- The Gravel Path Renovator can be used in conjunction with a tractor CAT 1 rear 3 point linkage on a wide range of tractor models.
- The WE range sport robust construction techniques, with CNC folded and welded, heavy gauge steel, making them lightweight and compact, but extremely tough.
- Low vibration is made possible by the contra rotating knife rotors.
- An oil bath gearbox reduces maintenance to a minimum.

For more info



## MECHANICAL DRIVE

### WE 110 M - DP

### WE 150 M - DP

Working width	110cm	150cm
Weight		
Drive Type	PTO	PTO
Connection type	CAT 1	CAT 1
Height setting	Castor Wheels	Roller

## Optional Accessories

1	Angled Knife set for water bound surfaces	WM-SATZ 110	WM-SATZ 150
2	Chesel Set with carbide tips for crushed stone and water bound	MEISSEL-SATZ 110	MEISSEL-SATZ 150
3	Thick weedbrush sections for tarmac sub base	BUES-SATZ 110	BUES-SATZ 150

## Mounting options for WE Series

The following options are the basic types of mounting systems. Within these broad categories are many individual varieties; particular to power unit or linkage manufactures. Precise details of mounting vehicle should be supplied to ensure correct fitment.

**ABR WE DP (INCLUDED)** - Tractor front linkage with CAT 1 or CAT 2 link arms. The bracket is fixed to the Path Renovator because tractor link arms provides float for the machine. Allows the path renovator to connect to link arms.



### ① Angled knife set

The WE Series is sold without tools. Tools must be selected for the application which the machine is being used for. The Angled knife set is for using on water bound surfaces. The knives can be lowered to the correct height so there is minimal interference with the sub base. The knives de-compact the surface. Not only this, but because of the angle, they can cut under the root of the weed and lift the whole plant to the surface, where it can be easily blown or raked off. This not only leaves the surface free of weeds, but also allows it to drain properly, and the filling to be distributed evenly across the path to avoid pot-holes.



### ② Chisel set with Carbide tips

An aggressive chisel set with carbide tips can be used to loosen extremely compacted surfaces made from crushed stone or water bound materials. Any weeds will be loosened by the chisels and can be picked out from the loose surface. This will restore the drainage properties of the surface and allow it to be distributed evenly across the path to avoid pot-holes.



### ③ Weed Brush set

The weed brush can also be fitted to the WE Series. This is for use on hard surfaces, such as tarmac or concrete. The brushes loosen the compacted gravel if present and also loosen soil and weeds from the hard surface, so it can be collected. This process will also allow any gravel to be evenly distributed across the surface to avoid pot-holes.

