

Kersten LBV and LBV MAX front or rear mounted blowers

CODE

DESCRIPTION

LBV-HO-FKDR



Leaf Blower for ride-on mowers (Front Mounting Only)

Lightweight Dynamically balanced alloy fan, 230km/h air velocity blowing material up to 8 metres. 60m³/min

Very low noise with inlet and exhaust baffles.

Manual adjustable outlet left, front and right.

13hp petrol engine,

Quick-Attach-A system

Requires FKDR Front Linkage system to mount it to a ride-on mower (see below)

Current applications include Kubota GR1600, GR2100, GR2120, G18, G21, G2160, John Deere X300, X540, Some LT. Grillo FD300, FD700. Viking T5, T6. Stiga Park, Villa. Iseki SXG 216, Castel Garden XHT21, New Holland GT75, Toro DH220, XL. Husqvarna R316T. Other application may be available on request.

FKDR



Front linkage kit for Ride-on Mowers

Manual lift and lower

Manual angling left and right

All actions from operators seat.

Quick-Attach-A system implement hitch.

To suit LBV above

FKDR-SPECIAL



Front linkage kit for Ride-on Mowers

Hydraulic lift and lower using oil supply from mowers own deck lift system

Manual angling left and right

All actions from operators seat

Quick-Attach-A implement hitch

To suit LBV above

LBV-M-ABR



LBV Tractor Mounted Low Noise Blower PTO drive.

Specify 540/1000/2000 rpm at time of order

LBV-H-ABR



LBV Tractor Mounted Low Noise Blower Hydraulic drive

Requires 24 litres/minute oil flow. Requires hydraulic service.

Lightweight Dynamically balanced alloy fan, 230km/h air velocity blowing material up to 8 metres. 60m³/min output capacity

Very low noise with inlet and exhaust baffles.

Manual adjustable outlet left, front and right.

Weight 85KG

ABR-LBV linkage required, see below.

LBV-MAX-M-ABR



LBV MAX Tractor Mounted Low Noise Blower PTO drive

Specify 540/1000/2000 rpm at time of order

LBV-MAX-H-ABR



LBV MAX Tractor Mounted Low Noise Blower hydraulic drive

Requires 24 litres/minute oil flow. Requires hydraulic service.

Lightweight Dynamically balanced alloy fan, 230km/h air velocity blowing material up to 8 metres. 80m³/min output capacity

Very low noise with inlet and exhaust baffles.

Manual adjustable outlet left, front and right.

Weight 95KG

ABR-LBV linkage required, see below.

BR-LBV-KD—



'A' frame linkage - CAT 0

BR-LBV-DP—



Three-point linkage Cat 0 and I

BR-LBV-FM—



Two point linkage for Up Front Mowers etc

LBV-HUT-HD



Powered 360° outlet chute for blower. Suitable for LBV and LBV Max.

Requires hydraulic service to operate

All Prices are subject to VAT.

Kersten (UK) Ltd reserve the right to change prices and specification at any time.

Kersten
SITE MAINTENANCE EQUIPMENT

Kersten UK Limited are sole UK distributor of Kersten Arealmaschinen GmbH of Rees, Germany. © Kersten (UK) Ltd. 2014